



AN ADDENDUM

TO

TENDER NO: KOFC/OT/MT/001/2020/2021

FOR

SUPPLY AND DELIVERY OF HFO, PETROL, DIESEL, OIL
AND LUBRICANTS

FIRM'S DETAILS

NAME.....

P O BOX

TEL NO:

EMAIL ADDRESS.....

SIGNATURE:

STAMP.....

1. Please effect the following changes to our Tender Number **KOFC/OT/MT/001/2020/2021**

a. **Invitation to Tender (Page 3)** – Amend to read: Tenders must be accompanied by a security in the form and amount specified in the tender document, on or before **Thursday 05 November, 2020**.

b. **Sealing and Marking of Tenders- 2.17.2 (b) (Page 11)** – Amend to read: Bear, tender number and name in the Invitation for Tenders and the words, **“DO NOT OPEN BEFORE,” Thursday 05 November, 2020 at 1000 Hrs (10AM)**

c. **Deadline for Submission of Tenders - 2.18 (Page 11)** – Amend to read Tenders must be received by the procuring entity at the address specified under paragraph 2.17.2 no later than **Thursday 05 November, 2020**.

d. **Opening of Tenders 2.20.1 (Page 12)** – Amend to read: The Procuring entity will open all tenders in the presence of tenderers’ representatives who choose to attend, at 1000hrs on **Thursday 05 November, 2020** and in the location specified in the Invitation to Tender.

d. **Pursuant to paragraph 2.10 Tender Prices (Page 19)** – Amend to read: Price (s) quoted **MUST** be inclusive of **14% VAT** and shall remain valid for at least 90 days from the closing date of the tender.

2. Kindly treat this addendum as part of the Original Tender dated **Tuesday 13 October 2020**.

3. Other details of the original tender to remain the same.

Yours faithfully,



S M MANAMBO
Major General
Managing Director

SPECIFICATIONS FOR ROTTO INJECT FLUID-SCREW COMPRESSOR OIL

S/No	TYPICAL CHARACTERISTICS	METHOD	UNIT	VALUE
1	ISO GRADE	ASTMD2422	-	46
2	VISCOSITY AT 40°C	ISO3104	mm ² /s	45.2
3	VISCOSITY INDEX, VI	ISO2909	-	130
4	POUR POINT	ISO3016	°C	-39
5	FLASH POINT (OPEN CUP)	ISO2592	°C	240
6	CONRAD SON RESIDUE	NFT60115	%	0.1
7	FOAMING SEQUENCE 1 (TENDENCY/RESISTENCY)	ISO6247	ml/ml	%

SPECIFICATIONS FOR ISO VG32 OIL

S/No	TYPICAL CHARACTERISTICS	UNIT	VALUE
1	Specific Gravity (15/4°C)	-	0.87
2	Viscosity at 40°C	mm ² /s	32
3	Viscosity at 100°C	mm ² /s	5.4
4	Viscosity Index, VI		100
5	Maximum Operating Temperature	°C	70
6	Minimum Operating Temperature	°C	-10
7	Strainer Resistance	-	1.0

SPECIFICATION FOR EMKARATE OIL, REFRIGERATION LUBRICANT COMPRESSOR OIL, RL68 SERIES POE TYPE

S/No	INDEX	MEASUREMENT METHOD	VALUE
1	Viscosity at 40°C	D445	65.5 CST
2	Viscosity at 100°C	D445	9.3 CST
3	Pour point	D97	-39°C
4	Density at 20°C	D1298	0.98
5	Flash Point	E92	270°C
6	Water Content	E106485	<40ppm
7	Acid Value	*	0.02mgKOH/g
8	Colour Hazen	D1209	70